			•	
VISIBLE	EMISSION	NOTATIONS		
Inspector:		·		

Shift: 1st Shift or 2st Shift Time:

1		- 1 8 - 1 C		
Unit	Visual Inspection NORMAL Or ABNORMAL		Coniments	
Visible Emission From Shaker	Nor	And the second s	2	
Visible Emission From Discharge Conveyor System	Nor	anamator"		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected a cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS


Visible Emission From
Discharge Conveyor System

noR

nor

Inspector: Smell Co					
Date of Inspection:	2.14				
Shift: 1st Shift or 2nd Shi	ft Tin	ne: 500			
Unit	Visual Inspection		Commer	its	Particular of the second of th
	<u>NÖR</u> MAL or				
Visible Emission From Shaker	ABNORMAL IO a O				THE PARTY OF THE P

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTA	TIONS		_	
Inspector:	1 Compto			
Date of Inspection: 5/3/	14			
Shift: 1 st Shift or (2 nd)Sh	ift Ti	me: 5AM		
Unit .	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nor	Chillips opposite (20 in 1996) and the contract of the contrac		
Visible Emission From Discharge Conveyor System	Nal			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	
Inspector: Str	Mu I				
Date of Inspection:	534				3
Shift: (1st Shift or 2st Sh	ift Ti	me:@1700	, .	,	• • .
Unit	Visual Inspection NORMAL For ABNORMAL		C	omments	
Visible Emission From Shaker	Non	**************************************			
Visible Emission From Discharge Conveyor System	Nac	spinor		ŧ.	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected a cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS /		_	
Inspector:	1 Campto	\nearrow		
Date of Inspection:	114			
Shift: 1 st Shift or (2 nd)Sh	ift Ti	me: 5AM		
	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	Nor		-	


- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

7101DEL 211110010	NOIDEL LIMICOTOR ROTATIONS						
Inspector:	Smelko						
Date of Inspection:	- 5-4-14						
Shift: 1 st Shift or	2 nd Shift	Time: 500					

Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL	Comments
Visible Emission From Shaker	nor	
Visible Emission From Discharge Conveyor System	nor	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTATIONS

Visible Emission From Discharge Conveyor System nog

non

Inspector: Smelke	>				
Date of Inspection: 5-5-14			-		
Shift: (st Shift) or 2 nd Sh	ift Ti	me: 500			
	Visual Inspection NORMAL Or ABNORMAL			Comments	Company of the Compan
Visible Emission From Shaker	10 - 0				

• Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.

• Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:	Cord Tel			
Date of Inspection:	5-6-2010			
Shift: 1 st Shift or 2 nd Sh		me: 5.30		
Unit	Visual Inspection NORMAL or		Comments	
Visible Emission From Shaker	ABNORMAL			<u>表现是不够多种的</u>
Visible Emission From Discharge Conveyor System	NAC	_		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		·		•
Inspector: Device	Cultoe		-		•
Date of Inspection:					f
Shift: 1 ⁵¹ Shift or (2 ¹¹⁰ Sh		me: 5:30			• •
Unit	Visual Inspection NORMAL Or ABNORMAL		Comments		
Visible Emission From Shaker	Nor			,	
Visible Emission From Discharge Conveyor System	Nor	· martine *		E.	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

AIGIDEE FINIOGICIA IAC IA	110110			
Inspector:				
Date of Inspection:			_	
Shift: 1st Shift or 2nd Sh	nift Tim	ne:	_	
Unit	Visual Inspection NORMAL or ABNORMAL			The second secon
Visible Emission From Shaker				
Visible Emission From Discharge Conveyor System				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Smed Ko	X			
Date of Inspection:	9,14			
Shift: 1 st Shift or 2 nd Sh	lift Ti	me: 500		
	Visual Inspection NORMAL or ABNORMAL		Comments was a superior of the comments of the	
Visible Emission From Shaker	noh			
Visible Emission From Discharge Conveyor System	noR	~		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.








VISIBLE EMISSION NOTATIONS Inspector: Date of Inspection: Shift: 1st Shift or 2nd Shift Time: Unit Visual Comments Inspection NORMAL Or: ABNORMAL Visible Emission From Shaker Visible Emission From Discharge Conveyor System

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSION NOTA	ATIONS		
Inspector:	Compton		
Date of Inspection:	1140		
Shift: 1 st Shift or (2 nd)Sh	nift Ti	me: SAM	
Unit de la company de la compa	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments Comments
Visible Emission From Shaker	No		
Visible Emission From Discharge Conveyor System	Ner		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTA	ATIONS			
Inspector: Smelko				
Date of Inspection: May	13,14			
Shift: 1 st Shift or 2 nd Sh	nift Ti	me: 500		
	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments Transcription of the comment of the comme	
Visible Emission From Shaker	nor	33		
Visible Emission From Discharge Conveyor System	nor	*Tallage*		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSION NOT	TIONS		_	
Inspector: Smelko				
Date of Inspection: May	14.14			
Shift: 1 st Shift or 2 nd Sh	lift Ti	me: 520		
	Visual Inspection NORMAL or ABNORMAL		Comments The property of the	
Visible Emission From Shaker	nor			
Visible Emission From Discharge Conveyor System	NOR	William .		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		_	
Inspector: 5me 1Ko				
Date of Inspection: May	15,04			
Shift: (1 st Shift or 2 nd Sh	nift Ti	me: 500		
	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments in the property of th	
Visible Emission From Shaker	nog			
Visible Emission From Discharge Conveyor System	nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:	aren Co	Joe		
Date of Inspection:	5-16-19	/		
Shift: 1 st Shift or 2 nd Sh	nift Ti	me: 530		
	Visual Inspection NORMAL or ABNORMAL		Comments Section 1 Sectio	(2.1 (4.1 (4.1 (4.1 (4.1 (4.1 (4.1 (4.1 (4
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	17			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

nor

Visible Emission From Discharge Conveyor System

Inspector: Smelko				
Date of Inspection:	18 14			
Shift: 1 st Shift or 2 nd Sh	iift	me: 560		
Unit	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	noR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

nor

Visible Emission From Discharge Conveyor System

71010EE EIIIICC101111017				
Inspector: Smelk	6			
Date of Inspection:	19,14			
Shift: (st Shift) or 2 nd Sh	ift Ti	me: \$ 26		
Unit	Visual Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	noR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSION NOTATIONS

Inspector: Smelfo		
Date of Inspection: May 20 14		
Shift: 1 st Shift or 2 nd Shift	Time: 5:00	

	Las arreste AVIII - VIII - VIII	Karagan panasa ang karang	<u> </u>	
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments Property of the Comments of the Comm	
Visible Emission From Shaker	nor			
Visible Emission From Discharge Conveyor System	nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

Discharge Conveyor System

nor

VIOLENZE ENTINOSION NO 17			_	
Inspector:	Smelko			
	may 21,14		7	
Shift: 1 st Shift or 2 nd Sh	ift Ti	me: 500		
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Commen	
Visible Emission From Shaker	nor-			
Visible Emission From				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.


VISIBLE EMISSION NOTA	TIONS		
Inspector: Smell	CO]
Date of Inspection:	22.14		
Shift: 1 st Shift or 2 nd Sh	ift Ti	me: 500	
Unit	Visual Inspection NORMAL or ABNORMAL		Comments All the second of th
Visible Emission From Shaker	<u>abnorvial</u> NoR		
Visible Emission From Discharge Conveyor System	nor	0000-	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

AIOIDEE EIMIOOIOIA IAO IA	110110		_		
Inspector: Smelk	>				
Date of Inspection: May	23,14				
Shift: 1st Shift or 2nd Sh	ift T	ime: 5.00			
Unit.	Visual Inspection NORMAL or ABNORMAL		Comments		
Visible Emission From Shaker	NOR			engener pungjungjar og en grengen gen fig migjengar til gjengar til gjengar til gjengar gre	and the second s
Visible Emission From Discharge Conveyor System	N C O	_			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTATIONS

AISIBLE EMISSION MOLY	ATIONS			
Inspector:	Stoomer			
Date of Inspection:	5/24/14			
Shift: 1 st Shift or 2 nd St	nift Ti	me: @ osco		
	Visual Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL		Comments property of the prop	
Visible Emission From Shaker	Nor	(4770ha)		
Visible Emission From Discharge Conveyor System	Nac	100		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS /			
Inspector:	7			
Date of Inspection:	onflor		_	
5/24	114			
Shift: 1 st Shift or 2 nd Sh	nift Ti	me: 5PM		
Unit	Visua) Inspection NORMAL Or ABNORMAL		Comments project Senten proj	
Visible Emission From Shaker	Nor		egymniaeth ersekann i sy gan glasiferrau gaeth ersekt fi bailean a thag and geal bac	
Visible Emission From Discharge Conveyor System	Nov	Processing and action and representative and repres		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				
Inspector: Sme	G				
Date of Inspection:	N 27,14				
Shift: 1 st Shift or 2 nd Sh	ift Ti	me: 500			_
Unit.	Visual Inspection NORMAL or ABNORMAL			Comments	
Visible Emission From Shaker	NoR	1000.00g	eli (1885) indi is saida a contraso del sendantic aprissor	<u>。 《《大學》,但是</u>	
Visible Emission From Discharge Conveyor System	NOR	allers.			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Darren A	id TOE			
Date of Inspection:				
Shift: 1 st Shift or 2 nd Sh	nift Ti	me: 5:30		
Unit	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	Nor			,

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.